




Closure	Rubber Seal Non-Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Precision	Abec 1
Radial Clearance	C3
Lubrication	L627 Polyrex EM Grease
Dynamic Load Capacity (Cr):	1584.90 lbs
Static Load Capacity (Cor):	1022.88 lbs
Max Speed Grease	16000 rpm
Max Speed Oil	19000 rpm

COMPONENT	METRIC SERIES NON-CONTACT SEAL	
6905-LLB-C3/L627 TPI BRAND 25 mm x 42 mm x 9 mm, Single Row Radial, Deep Groove Ball Ball Bearing, Two Non-Contact Rubber Seals	UNIT	
	mm	
	SHEET	



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com
www.pibsales.store

This file and any associated information
 and specifications are provided for
 reference and evaluation purposes only,
 and is subject to change without notice.
 PIB makes no representations, warranties
 or guarantees as to the appropriateness,
 accuracy, completeness, or suitability for
 any purpose, of the file, information or
 specifications. You are solely responsible
 for the use of the file, information or
 specifications.