






|                              |                                               |
|------------------------------|-----------------------------------------------|
| Brand                        | Ruland                                        |
| Screw Finish                 | Black Oxide                                   |
| Bore (B1)                    | 15 mm                                         |
| Bore (B2)                    | 0.3125 in                                     |
| Keyway                       | No                                            |
| B1 Max Shaft Penetration     | 0.804 in (20.4 mm)                            |
| B2 Max Shaft Penetration     | 0.804 in (20.4 mm)                            |
| Seating Torque               | 2.1 Nm                                        |
| Length (L)                   | 1.700 in (43.2 mm)                            |
| Bore Tolerance               | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm)   |
| ISO 9001:2015                | Certified                                     |
| REACH                        | Compliant                                     |
| RoHS3                        | Compliant                                     |
| Conflict Minerals            | Compliant                                     |
| Tariff Code                  | 8483.60.8000                                  |
| Number of Screws             | 2 ea                                          |
| O.D. (D)                     | 1.313 in (33.3 mm)                            |
| Material                     | Aluminum                                      |
| Screw Material               | Alloy Steel                                   |
| Dynamic Torque Reversing     | 30 lb-in (3.40 Nm)                            |
| Maximum Speed                | 10000 RPM                                     |
| Shaft Tolerance              | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm |
| Zero-Backlash?               | Yes                                           |
| Balanced Design              | Yes                                           |
| UNSPC                        | 31163018                                      |
| Cap Screw                    | M3                                            |
| Dynamic Torque Non-Reversing | 60 lb-in (6.80 Nm)                            |
| Hex Wrench Size              | 2.5 mm                                        |
| Torsional Stiffness          | 400 lb-in/Deg (45 Nm/Deg)                     |
| Static Torque                | 120 lb-in (13.6 Nm)                           |
| Angular Misalignment         | 1.5 deg                                       |
| Parallel Misalignment        | 0.006 in (0.15 mm)                            |
| Axial Motion                 | 0.016 in (0.40 mm)                            |
| Bellows Attachment Method    | Epoxy                                         |
| Length Tolerance             | +/- 0.030 in (0.76 mm)                        |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)                |
| Product Group                | Bellows Coupling Standard Length              |
| Recommended Hex Key          | Metric Hex Keys                               |



|           |                                  |
|-----------|----------------------------------|
| COMPONENT | Bellows Coupling Standard Length |
|-----------|----------------------------------|



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BC21-15MM-5/16"-A**  
**Ruland**  
15mm X 5/16" Bores, 1.313" (33.3mm), Od, 1.700" (43.2mm) Length,  
Bellows Coupling, High Stiffness, Aluminum

| UNIT        |
|-------------|
| Inch/Metric |
| SHEET       |