






|                              |                                               |
|------------------------------|-----------------------------------------------|
| Brand                        | Ruland                                        |
| Screw Finish                 | Black Oxide                                   |
| Bore (B1)                    | 0.7500 in                                     |
| Bore (B2)                    | 17 mm                                         |
| Keyway                       | No                                            |
| B1 Max Shaft Penetration     | 0.946 in (24.0 mm)                            |
| B2 Max Shaft Penetration     | 0.946 in (24.0 mm)                            |
| Seating Torque               | 4.6 Nm                                        |
| Length (L)                   | 2.035 in (51.7 mm)                            |
| Bore Tolerance               | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm)   |
| ISO 9001:2015                | Certified                                     |
| REACH                        | Compliant                                     |
| RoHS3                        | Compliant                                     |
| Conflict Minerals            | Compliant                                     |
| Tariff Code                  | 8483.60.8000                                  |
| Number of Screws             | 2 ea                                          |
| O.D. (D)                     | 1.625 in (41.3 mm)                            |
| Material                     | Aluminum                                      |
| Screw Material               | Alloy Steel                                   |
| Dynamic Torque Reversing     | 62.5 lb-in (7.00 Nm)                          |
| Maximum Speed                | 10000 RPM                                     |
| Shaft Tolerance              | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm |
| Zero-Backlash?               | Yes                                           |
| Balanced Design              | Yes                                           |
| UNSPC                        | 31163018                                      |
| Cap Screw                    | M4                                            |
| Dynamic Torque Non-Reversing | 125 lb-in (14.00 Nm)                          |
| Hex Wrench Size              | 3.0 mm                                        |
| Torsional Stiffness          | 550 lb-in/Deg (63 Nm/Deg)                     |
| Static Torque                | 250 lb-in (28.0 Nm)                           |
| Angular Misalignment         | 2.0 deg                                       |
| Parallel Misalignment        | 0.010 in (0.25 mm)                            |
| Axial Motion                 | 0.020 in (0.51 mm)                            |
| Bellows Attachment Method    | Epoxy                                         |
| Length Tolerance             | +/- 0.030 in (0.76 mm)                        |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)                |
| Product Group                | Bellows Coupling Standard Length              |
| Recommended Hex Key          | Metric Hex Keys                               |



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BC26-3/4"-17MM-A**  
**Ruland**  
3/4" X 17mm Bores, 1.625" (41.3mm), Od, 2.035" (51.7mm) Length,  
Bellows Coupling, High Stiffness, Aluminum

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |