





|                              |                                               |
|------------------------------|-----------------------------------------------|
| Brand                        | Ruland                                        |
| Length (L)                   | 1.700 in (43.2 mm)                            |
| Bore (B1)                    | 0.6250 in                                     |
| Bore (B2)                    | 10 mm                                         |
| Keyway                       | Yes                                           |
| Keyway (K1)                  | 3/16 in                                       |
| Keyway (K2)                  | 3 mm                                          |
| B2 Max Shaft Penetration     | 0.804 in (20.4 mm)                            |
| B1 Max Shaft Penetration     | 0.804 in (20.4 mm)                            |
| Screw Material               | Alloy Steel                                   |
| Bore Tolerance               | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm)   |
| Screw Finish                 | Black Oxide                                   |
| ISO 9001:2015                | Certified                                     |
| REACH                        | Compliant                                     |
| RoHS3                        | Compliant                                     |
| Conflict Minerals            | Compliant                                     |
| Tariff Code                  | 8483.60.8000                                  |
| O.D. (D)                     | 1.313 in (33.3 mm)                            |
| Material                     | Aluminum                                      |
| Number of Screws             | 2 ea                                          |
| Seating Torque               | 2.1 Nm                                        |
| Dynamic Torque Reversing     | 30 lb-in (3.40 Nm)                            |
| Product Group                | Bellows Coupling Standard Length              |
| Shaft Tolerance              | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm |
| Zero-Backlash?               | Yes                                           |
| Balanced Design              | Yes                                           |
| UNSPC                        | 31163018                                      |
| Cap Screw                    | M3                                            |
| Hex Wrench Size              | 2.5 mm                                        |
| Dynamic Torque Non-Reversing | 60 lb-in (6.80 Nm)                            |
| Static Torque                | 120 lb-in (13.6 Nm)                           |
| Torsional Stiffness          | 400 lb-in/Deg (45 Nm/Deg)                     |
| Angular Misalignment         | 1.5 deg                                       |
| Parallel Misalignment        | 0.006 in (0.15 mm)                            |
| Axial Motion                 | 0.016 in (0.40 mm)                            |
| Bellows Attachment Method    | Epoxy                                         |
| Length Tolerance             | +/- 0.030 in (0.76 mm)                        |
| Maximum Speed                | 10000 RPM                                     |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)                |
| Recommended Hex Key          | Metric Hex Keys                               |



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCK21-5/8"-10MM-A**  
**Ruland**  
5/8" X 10mm Bores, 1.313" (33.3mm), Od, 1.700" (43.2mm) Length,  
Bellows Coupling With Keyways, High Stiffness, Aluminum

| UNIT        |
|-------------|
| Inch/Metric |
| SHEET       |