





|                              |                                               |
|------------------------------|-----------------------------------------------|
| Brand                        | Ruland                                        |
| Number of Screws             | 2 ea                                          |
| Material                     | Aluminum                                      |
| Bore (B1)                    | 20 mm                                         |
| Bore (B2)                    | 0.6250 in                                     |
| Keyway                       | Yes                                           |
| Keyway (K1)                  | 6 mm                                          |
| Keyway (K2)                  | 3/16 in                                       |
| B2 Max Shaft Penetration     | 1.099 in (27.9 mm)                            |
| Bore Tolerance               | +0.001 in / -0.000 in (+0.03 mm / -0.00 mm)   |
| B1 Max Shaft Penetration     | 1.099 in (27.9 mm)                            |
| Screw Material               | Alloy Steel                                   |
| Screw Finish                 | Black Oxide                                   |
| ISO 9001:2015                | Certified                                     |
| REACH                        | Compliant                                     |
| RoHS3                        | Compliant                                     |
| Conflict Minerals            | Compliant                                     |
| Tariff Code                  | 8483.60.8000                                  |
| O.D. (D)                     | 2.000 in (50.8 mm)                            |
| Length (L)                   | 2.413 in (61.3 mm)                            |
| Static Torque                | 400 lb-in (45.2 Nm)                           |
| Dynamic Torque Non-Reversing | 200 lb-in (22.60 Nm)                          |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)                |
| Product Group                | Bellows Coupling Standard Length              |
| Shaft Tolerance              | +0.0000 in / -0.0005 in +0.000 mm / -0.013 mm |
| Zero-Backlash?               | Yes                                           |
| Balanced Design              | Yes                                           |
| UNSPC                        | 31163018                                      |
| Cap Screw                    | M5                                            |
| Hex Wrench Size              | 4.0 mm                                        |
| Seating Torque               | 9.5 Nm                                        |
| Dynamic Torque Reversing     | 100 lb-in (11.30 Nm)                          |
| Torsional Stiffness          | 950 lb-in/Deg (108 Nm/Deg)                    |
| Angular Misalignment         | 2.0 deg                                       |
| Parallel Misalignment        | 0.010 in (0.25 mm)                            |
| Axial Motion                 | 0.020 in (0.51 mm)                            |
| Bellows Attachment Method    | Epoxy                                         |
| Length Tolerance             | +/- 0.030 in (0.76 mm)                        |
| Maximum Speed                | 10000 RPM                                     |
| Recommended Hex Key          | Metric Hex Keys                               |



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**BCK32-20MM-5/8"-A**  
**Ruland**  
20mm X 5/8" Bores, 2.000" (50.8mm), Od, 2.413" (61.3mm) Length,  
Bellows Coupling With Keyways, High Stiffness, Aluminum

| UNIT        |
|-------------|
| Inch/Metric |
| SHEET       |