




Brand	Ruland
Screw Material	Alloy Steel
Material	Aluminum
Bore (B1)	16 mm
Bore (B2)	0.3125 in
Keyway	No
B1 Max Shaft Penetration	0.935 in (23.7 mm)
B2 Max Shaft Penetration	0.935 in (23.7 mm)
Seating Torque	2.1 Nm
Bore Tolerance	+0.001 in / -0.000 in (+0.03 mm / -0.00 mm)
Screw Finish	Black Oxide
ISO 9001:2015	Certified
REACH	Compliant
RoHS3	Compliant
Conflict Minerals	Compliant
Tariff Code	8483.60.8000
Number of Screws	2 ea
O.D. (D)	1.313 in (33.3 mm)
Length (L)	1.962 in (49.8 mm)
Static Torque	120 lb-in (13.6 Nm)
Maximum Speed	10000 RPM
Product Group	Bellows Coupling - Extended Length
Shaft Tolerance	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm
Zero-Backlash?	Yes
Balanced Design	Yes
UNSPC	31163018
Cap Screw	M3
Dynamic Torque Non-Reversing	60 lb-in (6.80 Nm)
Dynamic Torque Reversing	30 lb-in (3.40 Nm)
Hex Wrench Size	2.5 mm
Torsional Stiffness	300 lb-in/Deg (33.9 Nm/Deg)
Angular Misalignment	3.0 deg
Parallel Misalignment	0.012 in (0.30 mm)
Axial Motion	0.032 in (0.81 mm)
Bellows Attachment Method	Epoxy
Length Tolerance	+/- 0.030 in (0.76 mm)
Temperature	-40°F to 200°F (-40°C to 93°C)
Recommended Hex Key	Metric Hex Keys



COMPONENT

Bellows Coupling - Extended Length



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587 1-800-228-8895,
510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

BCL21-16MM-5/16"-A
Ruland
16mm X 5/16" Bores, 1.313" (33.3mm) Od., 1.962" (49.8mm) Length,
Bellows Coupling, Increased Misalignment, Aluminum

UNIT
Inch/Metric
SHEET