



|            |                                                  |
|------------|--------------------------------------------------|
| Brand      | Ruland                                           |
| Length (L) | 3.080 in (78.2 mm)                               |
| Note       | Stainless steel hubs are available upon request. |
| O.D. (D)   | 2.250 in (57.2 mm)                               |
| Material   | Aluminum                                         |



**Pacific International Bearing, Inc.**  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## COMPONENT

Disc Coupling - Double

**DCDK36-5/8"-15MM-A**  
**Ruland**  
 0.6250" X 15mm Bores, 2.250" (57.2mm)  
 Od, And 3.080" (78.2mm) Length, 3/16" X  
 5mm Keyways, Clamp Double Disc  
 Coupling, Anodized Aluminum Hubs,  
 Stainless Steel Disc Springs, And A  
 Center Spacer

UNIT

Inch/Metric

SHEET