






|                              |                                  |
|------------------------------|----------------------------------|
| Brand                        | Ruland                           |
| Screw Material               | Alloy Steel                      |
| Material                     | Aluminum                         |
| Bore (B1)                    | 14 mm                            |
| Bore (B2)                    | 12 mm                            |
| Keyway                       | No                               |
| B1 Max Shaft Penetration     | 24.0 mm                          |
| B2 Max Shaft Penetration     | 24.0 mm                          |
| Seating Torque               | 4.6 Nm                           |
| Bore Tolerance               | +0.03 mm / -0.00 mm              |
| Screw Finish                 | Black Oxide                      |
| ISO 9001:2015                | Certified                        |
| REACH                        | Compliant                        |
| RoHS3                        | Compliant                        |
| Conflict Minerals            | Compliant                        |
| Tariff Code                  | 8483.60.8000                     |
| Number of Screws             | 2 ea                             |
| O.D. (D)                     | 1.625 in (41.3 mm)               |
| Length (L)                   | 2.035 in (51.7 mm)               |
| Static Torque                | 28.0 Nm                          |
| Maximum Speed                | 10000 RPM                        |
| Product Group                | Bellows Coupling Standard Length |
| Shaft Tolerance              | +0.000 mm / -0.013 mm            |
| Zero-Backlash?               | Yes                              |
| Balanced Design              | Yes                              |
| UNSPC                        | 31163018                         |
| Cap Screw                    | M4                               |
| Dynamic Torque Non-Reversing | 14.00 Nm                         |
| Dynamic Torque Reversing     | 7.00 Nm                          |
| Hex Wrench Size              | 3.0 mm                           |
| Torsional Stiffness          | 63 Nm/Deg                        |
| Angular Misalignment         | 2.0 deg                          |
| Parallel Misalignment        | 0.25 mm                          |
| Axial Motion                 | 0.50 mm                          |
| Bellows Attachment Method    | Epoxy                            |
| Length Tolerance             | +/- 0.76 mm                      |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)   |
| Recommended Hex Key          | Metric Hex Keys                  |



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBC41-14-12-A**  
**Ruland**  
14mm X 12mm Bores, 41.3mm Od, 51.7mm Length, Bellows Coupling,  
High Stiffness, Aluminum

UNIT

Metric

SHEET