




Brand	Ruland
Hex Wrench Size	6.0 mm
Material	Aluminum
Bore (B1)	35 mm
Bore (B2)	25 mm
Keyway	No
B1 Max Shaft Penetration	40.2 mm
B2 Max Shaft Penetration	40.2 mm
Screw Material	Alloy Steel
Screw Finish	Black Oxide
Bore Tolerance	+0.03 mm / -0.00 mm
ISO 9001:2015	Certified
REACH	Compliant
RoHS3	Compliant
Conflict Minerals	Compliant
Tariff Code	8483.60.8000
Number of Screws	2 ea
Seating Torque	39 Nm
O.D. (D)	2.750 in (69.9 mm)
Length (L)	3.431 in (87.1 mm)
Dynamic Torque Reversing	26.13 Nm
Torsional Stiffness	237 Nm/Deg
Shaft Tolerance	+0.000 mm / -0.013 mm
Zero-Backlash?	Yes
Balanced Design	Yes
UNSPC	31163018
Cap Screw	M8
Static Torque	104.5 Nm
Dynamic Torque Non-Reversing	52.25 Nm
Temperature	-40°F to 200°F (-40°C to 93°C)
Maximum Speed	10000 RPM
Angular Misalignment	2.0 deg
Parallel Misalignment	0.30 mm
Axial Motion	0.76 mm
Bellows Attachment Method	Epoxy
Length Tolerance	+/- 0.76 mm
Recommended Hex Key	Metric Hex Keys
B1 Min Shaft Penetration	19.1 mm
Product Group	Bellows Coupling Standard Length
B2 Min Shaft Penetration	19.1 mm



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587 1-800-228-8895,
510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MBC70-35-25-A
Ruland
35mm X 25mm Bores, 69.9mm, Od, 87.1mm Length, Bellows Coupling,
High Stiffness, Aluminum

UNIT
Metric
SHEET