






|                              |                                  |
|------------------------------|----------------------------------|
| Brand                        | Ruland                           |
| Bore Tolerance               | +0.03 mm / -0.00 mm              |
| O.D. (D)                     | 1.625 in (41.3 mm)               |
| Material                     | Aluminum                         |
| Bore (B1)                    | 19 mm                            |
| Bore (B2)                    | 13 mm                            |
| Keyway                       | No                               |
| B1 Max Shaft Penetration     | 24.0 mm                          |
| Number of Screws             | 2 ea                             |
| Length (L)                   | 2.316 in (58.8 mm)               |
| Screw Material               | Alloy Steel                      |
| Screw Finish                 | Black Oxide                      |
| ISO 9001:2015                | Certified                        |
| REACH                        | Compliant                        |
| RoHS3                        | Compliant                        |
| Conflict Minerals            | Compliant                        |
| Tariff Code                  | 8483.60.8000                     |
| B2 Max Shaft Penetration     | 24.0 mm                          |
| Seating Torque               | 4.6 Nm                           |
| Cap Screw                    | M4                               |
| Static Torque                | 28.0 Nm                          |
| Temperature                  | -40°F to 200°F (-40°C to 93°C)   |
| Product Group                | Bellows Coupling Standard Length |
| Shaft Tolerance              | +0.000 mm / -0.013 mm            |
| Zero-Backlash?               | Yes                              |
| Balanced Design              | Yes                              |
| UNSPC                        | 31163018                         |
| Hex Wrench Size              | 3.0 mm                           |
| Maximum Speed                | 10000 RPM                        |
| Dynamic Torque Non-Reversing | 14.00 Nm                         |
| Dynamic Torque Reversing     | 7.00 Nm                          |
| Torsional Stiffness          | 39.4 Nm/Deg                      |
| Angular Misalignment         | 3.0 deg                          |
| Parallel Misalignment        | 0.38 mm                          |
| Axial Motion                 | 0.76 mm                          |
| Bellows Attachment Method    | Epoxy                            |
| Length Tolerance             | +/- 0.76 mm                      |



COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587 1-800-228-8895,  
510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCL41-19-13-A**  
**Ruland**  
19mm X 13mm Bores, 41.3mm, Od, 58.8 Mm Length, Bellows  
Coupling, Increased Misalignment, Aluminum

UNIT

Metric

SHEET