



|            |                                                  |
|------------|--------------------------------------------------|
| Brand      | Ruland                                           |
| Length (L) | 1.374 in (34.9 mm)                               |
| Note       | Stainless steel hubs are available upon request. |
| O.D. (D)   | 1.000 in (25.4 mm)                               |
| Material   | Aluminum                                         |

# COMPONENT

Disc Coupling - Double



**Pacific International Bearing, Inc.**  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MDCD25-9-8-A**  
**Ruland**  
 9mm X 8mm Bores, 25.4mm Od, And  
 34.9mm Length, Clamp Single Disc  
 Coupling, Accommodates All Types Of  
 Misalignment, Anodized Aluminum Hubs,  
 Stainless Steel Disc Springs, And A  
 Center Spacer

UNIT

Metric

SHEET