



|            |                                                  |
|------------|--------------------------------------------------|
| Brand      | Ruland                                           |
| Length (L) | 2.519 in (64.0 mm)                               |
| Note       | Stainless steel hubs are available upon request. |
| O.D. (D)   | 2.000 in (50.8 mm)                               |
| Material   | Aluminum                                         |

## COMPONENT

Disc Coupling - Double



**Pacific International Bearing, Inc.**  
 33258 Central Ave, Union City, CA 94587  
 1-800-228-8895, 510-512-7000,  
[info@pibsales.com](mailto:info@pibsales.com)  
[www.pibsales.com](http://www.pibsales.com)

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## MDCDK51-24-12-A Ruland

24mm X 12mm Bores, 50.8mm Od,  
 64.0mm Length, 8mm X 4mm Keyways,  
 Clamp Double Disc Coupling, Anodized  
 Aluminum Hubs, Stainless Steel Disc  
 Springs, And A Center Spacer

UNIT

Metric

SHEET