






|                              |                                 |
|------------------------------|---------------------------------|
| Brand                        | Ruland                          |
| Screw Material               | Alloy Steel                     |
| Material                     | 303 Stainless Steel             |
| Bore (B1)                    | 9 mm                            |
| Bore (B2)                    | 9 mm                            |
| Keyway                       | No                              |
| B1 Max Shaft Penetration     | 14.7 mm                         |
| B2 Max Shaft Penetration     | 14.7 mm                         |
| Number of Screws             | 2 ea                            |
| O.D. (D)                     | 1.000 in (25.4 mm)              |
| Screw Finish                 | Black Oxide                     |
| ISO 9001:2015                | Certified                       |
| REACH                        | Compliant                       |
| RoHS3                        | Compliant                       |
| Conflict Minerals            | Compliant                       |
| Tariff Code                  | 8483.60.8000                    |
| Bore Tolerance               | +0.025 mm / -0.000 mm           |
| Seating Torque               | 4.6 Nm                          |
| UNSPC                        | 31163003                        |
| Cap Screw                    | M4                              |
| Temperature                  | -40°F to 350°F (-40°C to 176°C) |
| Country of Origin            | USA                             |
| Product Group                | P-Series 4 Beam Couplings Clamp |
| Shaft Tolerance              | +0.000 mm / -0.013 mm           |
| Zero-Backlash?               | Yes                             |
| Balanced Design              | Yes                             |
| Hex Wrench Size              | 3.0 mm                          |
| Maximum Speed                | 6000 RPM                        |
| Static Torque                | 4.63 Nm                         |
| Dynamic Torque Non-Reversing | 2.32 Nm                         |
| Dynamic Torque Reversing     | 1.16 Nm                         |
| Torsional Stiffness          | 0.91 Deg/Nm                     |
| Angular Misalignment         | 3.0 deg                         |
| Parallel Misalignment        | 0.38 mm                         |
| Axial Motion                 | 0.25 mm                         |



COMPONENT

P-Series Four Beam Coupling



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**PCMR25-9-9-SS**

**Ruland**

9mm X 9mm Bores, 25.4mm Od, 31.8mm Length, Four Beam  
Coupling, Stainless Steel Clamp Style

UNIT

Metric

SHEET