






|                              |                                 |
|------------------------------|---------------------------------|
| Brand                        | Ruland                          |
| Screw Material               | Alloy Steel                     |
| Material                     | 303 Stainless Steel             |
| Bore (B1)                    | 0.5000 in                       |
| Bore (B2)                    | 0.3750 in                       |
| Keyway                       | No                              |
| B1 Max Shaft Penetration     | 0.695 in                        |
| B2 Max Shaft Penetration     | 0.695 in                        |
| Number of Screws             | 2 ea                            |
| O.D. (D)                     | 1.250 in (31.8 mm)              |
| Screw Finish                 | Black Oxide                     |
| ISO 9001:2015                | Certified                       |
| REACH                        | Compliant                       |
| RoHS3                        | Compliant                       |
| Conflict Minerals            | Compliant                       |
| Tariff Code                  | 8483.60.8000                    |
| Bore Tolerance               | +0.001 in / -0.000 in           |
| Seating Torque               | 4.6 Nm                          |
| UNSPC                        | 31163003                        |
| Cap Screw                    | M4                              |
| Temperature                  | -40°F to 350°F (-40°C to 176°C) |
| Country of Origin            | USA                             |
| Product Group                | P-Series 4 Beam Couplings Clamp |
| Shaft Tolerance              | +0.0000 in / -0.0005 in         |
| Zero-Backlash?               | Yes                             |
| Balanced Design              | Yes                             |
| Hex Wrench Size              | 3.0 mm                          |
| Maximum Speed                | 6000 RPM                        |
| Static Torque                | 70 lb-in                        |
| Dynamic Torque Non-Reversing | 35 lb-in                        |
| Dynamic Torque Reversing     | 17.5 lb-in                      |
| Torsional Stiffness          | 0.064 Deg/lb-in                 |
| Angular Misalignment         | 3.0 deg                         |
| Parallel Misalignment        | 0.015 in                        |
| Axial Motion                 | 0.010 in                        |



COMPONENT

P-Series Four Beam Coupling



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**PCR20-8-6-SS**  
**Ruland**  
1/2" X 3/8" Bores, 1.250" Od, 1.500" Length, Four Beam Coupling,  
Stainless Steel Clamp Style

UNIT

Inch

SHEET