




Brand	Ruland
Bore Tolerance	+0.001 in / -0.000 in
Tariff Code	8483.60.8000
Conflict Minerals	Compliant
RoHS3	Compliant
REACH	Compliant
ISO 9001:2015	Certified
Screw Finish	Black Oxide
Number of Screws	4 ea
Screw Material	Alloy Steel
B2 Max Shaft Penetration	0.695 in
B1 Max Shaft Penetration	0.695 in
Keyway	No
Bore (B2)	0.3750 in
Bore (B1)	0.5000 in
Material	Aluminum
O.D. (D)	1.250 in (31.8 mm)
Hex Wrench Size	3.0 mm
UNSPC	31163003
Parallel Misalignment	0.015 in
Angular Misalignment	3.0 deg
Torsional Stiffness	0.120 Deg/lb-in
Dynamic Torque Reversing	13 lb-in
Dynamic Torque Non-Reversing	26 lb-in
Static Torque	52 lb-in
Forged Set Screw	M6
Seating Torque	7.2 Nm
Zero-Backlash?	Yes
Shaft Tolerance	+0.0000 in / -0.0005 in
Product Group	P-Series 4 Beam Couplings Set Screw
Country of Origin	USA
Temperature	-40°F to 225°F (-40°C to 107°C)
Maximum Speed	6000 RPM
Axial Motion	0.010 in



COMPONENT

P-Series Four Beam Coupling



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PSR20-8-6-A
Ruland
1/2" X 3/8" Bores, 1.250" Od, 1.500" Length, Four Beam
Coupling, Aluminum Set Screw Style

UNIT

Inch

SHEET