




Non-contact sealed type (LLB)

Bore Diameter (d)	0.5 in
Outside Diameter (D)	1.125 in
Width (B)	0.3125 in
Closure	Rubber Seal Non-Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Brand	TPI
Precision	Abec 1
Radial Clearance	C3
Lubrication	L627 Polyrex EM Grease
Dynamic Load(Cr)	1146.53 lbs
Static Load(C0r)	537.29 lbs



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT	INCH SERIES SEALED	
R8-LLB-C3/L627 TPI 0.5 In X 1.125 In X 0.3125 In, Single Row Radial, Deep Groove Ball Bearing, Two Non-contact Rubber Seals	UNIT	
	INCH	
	SHEET	