



Brand	Ruland
Yoke Length (LY)	1.125 in
O.D. (D)	0.620 in
Bore (B1)	0.2500 in
Bore (B2)	0.2500 in
Keyway	No
B1 Max Shaft Penetration	0.820 in
B2 Max Shaft Penetration	0.820 in
Rated Torque	135 in-lb
Bore Tolerance	+0.0010 in / -0.0000 in
Joint Outer Diameter (OD)	0.620 in
Max Operating Angle	45
Material	Alloy Steel
Screw Material	Alloy Steel
Hub Depth (LH)	0.820 in
Screw Finish	Black Oxide
Forged Clamp Screw	M2
Recommended Lubricant	LUBRIPLATE No. 1200-2
Matching Boot Cover	UBOOT10/15-NI-KIT
ISO 9001:2015	Yes
REACH	Yes
RoHS3	Yes
Conflict Minerals	Compliant
Tariff Code	8483.60.4000
Product Group	Universal Joints - Clamp Style
Length (L)	2.250 in

COMPONENT

Single Universal Joint



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

USCL10-4-4-F

Ruland

1/4" X 1/4" Single Universal Joint, 0.620" Od,
2.250" Length, Friction Bearing, Steel, Clamp,
Coupling

UNIT

Inch

SHEET