



| | |
|---------------------------|--|
| Brand | Ruland |
| Yoke Length (LY) | 1.688 in |
| O.D. (D) | 0.995 in |
| Bore (B1) | 0.5000 in |
| Bore (B2) | 0.5000 in |
| Keyway | No |
| B1 Max Shaft Penetration | 1.190 in |
| B2 Max Shaft Penetration | 1.190 in |
| Rated Torque | 315 in-lb |
| Bore Tolerance | +0.0010 in / -0.0000 in |
| Joint Outer Diameter (OD) | 0.995 in |
| Max Operating Angle | 45 |
| Material | Stainless Steel |
| Screw Material | 18-8 300 Series Stainless Steel with Nypatch |
| Hub Depth (LH) | 1.190 in |
| Screw Finish | Bright |
| Forged Clamp Screw | M4 |
| Recommended Lubricant | LUBRIPLATE No. 1200-2 |
| Matching Boot Cover | UBOOT16/25-NI-KIT |
| ISO 9001:2015 | Yes |
| REACH | Yes |
| RoHS3 | Yes |
| Conflict Minerals | Compliant |
| Tariff Code | 8483.60.4000 |
| Product Group | Universal Joints - Clamp Style |
| Length (L) | 3.380 in |

COMPONENT

Single Universal Joint



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

USCL16-8-8-SS

Ruland

1/2" X 1/2" Single Universal Joint, 0.995" Od,
3.380" Length, Friction Bearing, Steel, Clamp,
Stainless Steel, Clamp, Coupling

UNIT

Inch

SHEET